

Introduction to GP programming

B. Allombert

IMB
CNRS/Université de Bordeaux

16/04/2018



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement N° 676541

Start by creating a text file `prog.gp` with the following content :

```
dist(a,b) = sqrt(a^2+b^2);
```

and save it. Under GP do (without hitting return) :

```
\r
```

Under Windows drag the file icon to the windows to complete the name :

```
\r .../prog.gp
```

On Linux you can just type the name. Call the function :

```
? dist(1,2)
%1 = 2.2360679774997896964091736687312762354
```

In a GP file, line ending terminates the line unless they are preceded by = or \ or are in a section delimited by braces :

```
cmpz(a,b) = if (abs(a)>abs(b), print(a), print(b))  
cmpz(a,b) =  
    if (abs(a)>abs(b), print(a), print(b))  
cmpz(a,b) = if (abs(a)>abs(b), \  
                print(a), \  
                print(b))  
  
cmpz(a,b) =  
{  
    if (abs(a)>abs(b),  
        print(a)  
    ,print(b))  
}  
}
```

Example of function

Add to the file `prog.gp`

```
fibo(n)=  
{  
    my(u0=0,u1=1);  
    for(i=2,n,  
        [u0,u1]=[u1,u0+u1]);  
    u1;  
}
```

and try

```
? \r  
? fibo(100)
```

- ▶ Put the opening brace on the line after the = sign.
- ▶ End the function by a semicolon.
- ▶ Declare any local variables with my () .
- ▶ Do not declare the loop index : it is local to the loop anyway.
- ▶ The function return value is the last computed value.
- ▶ Indent your code following the example.

While loop

Add

```
rho(n)=  
{  
    my(x=2,y=5);  
    while(gcd(y-x,n)==1,  
          x=(x^2+1)%n;  
          y=(y^2+1)%n;  y=(y^2+1)%n  
    );  
    gcd(n,y-x);  
}
```

and do

```
\r  
rho(2^64+1)  
%1 = 274177
```

control flow

```
wieferich(n)=  
{  
    forprime(p=2,n,  
        if(Mod(2,p^2)^(p-1)==1,  
            return(p)));  
}  
wieferich2(n)=  
{  
    my(r);  
    forprime(p=2,n,  
        if(Mod(2,p^2)^(p-1)==1,r=p;break));  
    r;  
}  
? wieferich(10000)  
%4 = 1093
```

Constructors

```
? V=vector(10,i,1/i)
%1 = [1,1/2,1/3,1/4,1/5,1/6,1/7,1/8,1/9,1/10]
? [1/i|i<-[1..10]]
%2 = [1,1/2,1/3,1/4,1/5,1/6,1/7,1/8,1/9,1/10]
? M=matrix(4,4,i,j,i*j)
%3 = [1,2,3,4;2,4,6,8;3,6,9,12;4,8,12,16]
```

The variables i and j are local and must not be declared.

forvec

Instead of

```
s3(n)=  
{  
    my(m=sqrtint(n));  
    for (i=1,m,  
        for (j=1,m,  
            for (k=1,m,  
                if (i^2+j^2+k^2==n,  
                    return([i,j,k]))));  
}  
? s3(12345)  
%2 = [4, 77, 80]
```

forvec

```
use forvec
```

```
s3(n)=  
{  
    my(m=sqrtint(n));  
    forvec(v=vector(3,i,[1,m]),  
        if (v*v~==n,  
            return(v)));  
}  
? s3(12345)  
%2 = [4, 77, 80]
```

For a better algorithm, see qfsolve.

associative array

```
birthday(n)=  
{  
    my(M = Map());  
    for(i=1,oo,  
        my(x=random(n), j);  
        if(mapisdefined(M,x,&j),  
            return([i,j]));  
        mapput(M,x,i));  
    }  
? birthday(2^30)  
%2 = [417,383]
```